



HIGH ADHESION ACRYLIC FLASHING TAPE

Key Features and Benefits

- Meets AAMA 711-13, ICC AC148 compliant, Voluntary Specification for Self Adhering Flashing Tape for Installation of Exterior Wall Fenestration Products, Type A (no primer), Class 3 (up to 176 degree F).
- Hand tearable No cutting tools required
- Lightweight 50-70 % lighter than conventional window flashing tapes
- Nail Sealable Passed AAMA-711-13 (ASTM D 1970)
- Repositionable No wrinkles when applied
- No scrap from adhesive side contact by mistake Clean, no black specks or stains, no asphalt smell
- High dimensional stability No wrinkling caused by temperature fluctuation
- Wide application temperature From -40°F to +176°F

- High temperature resistance No tensile strength losses after 45 weeks @ 194° F
- Very strong adhesion to rough surfaces
- Low water vapor transmittance < 1 Perm (20ng/Pa/sec/m2)
- Excellent durability against sunshine
- Compatible with building sealants Nichigo G-Tape™ is inert against sealant polymers, synthetic rubber compound, polyurethane, and silicone
- Clean emission No regulated chemical compounds in VOC from 3040BK



PART NO.	SIZE	DESCRIPTION	COLOR
GT3040BK02	2' x 65'	Nichigo G-Tape™ 3040BK	Black
GT3040BK04	4' x 65'	Nichigo G-Tape™ 3040BK	Black
GT3040BK06	6' x 65'	Nichigo G-Tape™ 3040BK	Black
GT3040BK09	9' x 65'	Nichigo G-Tape™ 3040BK	Black
GT3040BK12	12' x 65'	Nichigo G-Tape™ 3040BK	Black