

How To's & Helpful Hints

EZ Thin Tile Cutter Series

EZ Slimline, Pistol, T-Cutter, Running Plier

Part No.		Description
KEC-600	Up to 24"	EZ Thin Panel T-Cutter 24"
KEC-1500	Up to 60"	EZ Thin Panel T-Cutter 60"
KOC303B	Straight Cuts	EZ Pistol Type Oil Cutter
KOC305B	Straight Cuts	EZ Slimline Oil Cutter
KOC512P	Thicknesses 5mm to 12mm	EZ Glass Running Plier
5480-1700	-	EZ Thin Cutter Starter Kit (inc.T-Cutter, Pistol Cutter, Plier & Oil)
KOC1000	EZ Tile Cutter Lubrication	EZ Cutter Oil - 8oz. (237ml)

How to Use

- Open the self-lubricating reservoir and fill with the Alpha® EZ Cutter Oil (Part No. KOC1000)
- Before making the score, test to make sure that the EZ Cutter is dispensing oil.
- Align the Alpha® Spike Ruler to the line on the material that needs to be scored if you are using the Slimline or Pistol Type Oil Cutters. If you are using the T-Cutter, you do not need the Spike Ruler.
- Place the EZ Cutters scoring wheel on the edge of the material, while applying consistent down pressure pull the EZ Cutter towards you in a continuous non stopping motion till you reach the end of the material.
- Close the self-lubricating reservoir.
- Position the Alpha® Running Pliers (Part No. KOC512P) on the score mark and squeeze the handles to apply pressure on the scored material. The material will snap following the score mark across the material. **TIP: Teaming up and using two Alpha® EZ Glass Running Pliers at the same time with one on each side of the long panel is optional but recommended so the snapped panel does not get damaged.**
- If the material has fiberglass on the back surface, you will need to use a razor blade to cut the fiber glass after the material has been snapped.
- It is recommended after the material has been scored and snapped, use the Alpha® Electroplated Hand Pads (#60 or #150 grit) to remove the sharp edges. (Part No. DHP0060 or DHP0150)

Helpful Hints

- Use the Alpha® Spike Ruler for precision scoring with the EZ Thin Tile Cutters.
- Replacement cutting head for the EZ T-Cutter is available for purchase, Part No. KEC1902
- While applying consistent down pressure, pull the EZ Cutter towards you in a continuous non-stopping motion till you reach the end of the material. This will allow you to achieve a successful score mark on the surface of the material.
- An automatic oil feed dispenser is included within the packaging of the EZ Thin Tile Cutter (Slimline & Pistol Type) Oil Cutters to help you fill the reservoirs chambers with the EZ Cutter Oil.
- Video of the EZ Thin Tile Cutters in action is located on the product page of our website:
- Teaming up and using two Alpha® EZ Glass Running Pliers at the same time with one individual on each side of the long panel is optional but recommended so the snapped panel does not get damaged.