


# Alpha<sup>®</sup> Ecoguard Type W Dust Collection Cover Instruction Manual



Part No: ECOGRDCW Version 2



103 Bauer Drive, Oakland, NJ 07436 • 800-648-7229 • Fax: 800-286-0114 www.alpha-tools.com

## ►TABLE OF CONTENTS

Introduction	3
About the Symbols	3
Ecoguard Type W Overview	4
Accessories	4
Connectors & Flanges	5
Installation of the Dust Collection Cover	6
Installing to Alpha <sup>®</sup> or Makita <sup>®</sup> High-speed Angle Grinder	6
Installing to other High-speed Angle Grinders with	
included other connectors	7
Mounting the Diamond Wheel	7
Adjusting the Cutting Depth	8
Attaching the Dust Collector	9
Ecoguard Type W Schematic	.10
Ecoguard Type W Parts List	11

## ► INTRODUCTION

Thank you for purchasing the Alpha® Ecoguard "Type W" Dust Collection Cover. The Ecoguard Type W must be used with a vacuum, or other dust collection system. To ensure correct use, read this Instruction Manual and the Instruction Manual for the power tool and follow the operating instructions. Keep this manual in a place where operators can access it easily whenever necessary!

## ABOUT THE SYMBOLS

According to the hazard level, all safety notes in this manual are classified into "DANGER", "WARNING", and "CAUTION".

🛆 DANGER!	Deathorseriouspersonalinjuryisimminentwhenhandling	
	this polisher incorrectly.	

WARNING! There is a possibility of deathors erious personal injury when handling this polisher incorrectly.


CAUTION! There is a possibility of personal injury or property damage when handling this polisher incorrectly.

Note: In some situations, failing to observe WARNING notes could result in death or serious personal injury. Be sure to read and observe the safety notes to ensure safety and correct use of the polisher.

▶ PRECAUTIONS FOR USING DUST COLLECTION COVER

- 1. The Dust Collection Cover is for use with a 4.5" (115mm) and 5" (125mm) high-speed angle grinder.
- 2. The Dust Collection Cover is designed for cutting concrete, stone and other masonry products. Do not use when cutting metal or other materials.
- 3. The Dust Collection Cover is solely designed for use with a diamond cutting wheel. Do not use with any other type of blade such as a conventional abrasive blade or carbide tip saw blade.
- 4. Always check the Dust Collection Cover for damage, cracks or deformation before starting work. Do not use the Dust Collection Cover if it is damaged, cracked or bent as this could cause to injury.
- 5. Always wear eye protection. Dust mask, nonskid safety shoes, hard hat, or hearing protection must be used for appropriate conditions.
- 6. Keep the Dust Collection Cover away from gasoline, thinner, petroleum and paraffin.
- 7. The supplied connector may not connect securely to every high-speed angle grinder. In this case, do not use the Dust Collection Cover.

## ► ECOGUARD TYPE W OVERVIEW



## ► ACCESSORIES

Ecoguard Dust Collection Cover w/ Connector (Part# 500002)1 pc
Collar2 pcs
Additional Connector Assembly for Most 5" Grinders
Flange and Locknut Set for Selective Grinders1 set
Hex Wrench1 pc
Rubber Hose Adapter1 pc
Spacers2 pcs
Stainless Steel Hose Band1 pc
Pin Wrench1 pc

## ATTACHABLE GRINDERS

GRINDER	SIZE	MODEL
<b>ALPHA®</b>	5″	HSG-125
		GA4530
		GA4534
	4-1/2″	9564CV
		9564PC
		9557NB
		9557PB
		GA5010Z
MAKITA		GA5020
WANTA	5″	GA5020Y
	5	9558PB
		9565CV
		9565PC
		GA6020
	6″	GA6010Z
		9566CV
		9566PC
		G12SA3
		G12SE2
	4-1/2″	G12SE2P9
		G12SVA
HITACHI		G12SR3
		G12SS
	5″	G13SC2
		G13SC2P9
		G13SP
		G13VA


## ATTACHABLE GRINDERS (CONT'D)

GRINDER	SIZE	MODEL
		1800
	4-1/2″	1810PS
		1810PSD
		1801
BOSCH		1803EVS
возсп	5″	1811PS
		1821
		1821D
	6″	1806E
	0	1812PSD
	1.4/0 -	W8-115
	4-1/2″	W8-115 Quick
		W8-115 QuickProtect
		W8-125 Quick
		W11-125 Quick
		WA11-125 Quick
		WE9-125 Quick
	5″	WE14-125 Plus
METABO		WE14-125 VS
		WP8-125 QuickProtect
		WP11-125 QuickProtect
		WEPA14-125 QuickProtect
		W11-150 Quick
		WE14-150 Quick
	6″	WEP14-150 QuickProtect
		WEPA14-150 QuickProtect
		WP11-150 QuickProtect

## ATTACHABLE GRINDERS

GRINDER	SIZE	MODEL
DEWALT		D28110
	4-1/2″	D28112
		D28402
	4-1/2" / 5"	D28065
		D28114
		D28115
		D28131
	<i></i>	D28140
	6″	D28144
		6130-33
		6140-30
		6146-30
	4/1/2″	6146-31
		6146-33
		6147-30
		6147-31
		6121-30
		6121-31
MILWAUKEE		6117-30
	5″	6117-31
		6117-33
		6117-33D
		6121-31A
	6″	6124-30
		6124-31
		6161-30
		6161-31
		6161-33

### ► ECOGUARD TYPE W SPACERS AND CONNECTORS





# \Lambda WARNING!

- 1. Be sure to turn off the high-speed angle grinder and remove the plug from the electrical outlet before attaching and installing the Dust Collection Cover.
- 2. Make sure the Dust Collection Cover is securely attached; otherwise it may come loose which could cause injury.
- 3. If you installed the Dust Collection Cover to a high-speed angle grinder but the connector is loose and can not be securely attached, do not use the Dust Collection Cover. Using it in this state could cause injury.

► INSTALLING TO ALPHA® OR MAKITA® HIGH-SPEED ANGLE GRINDER

- 1. Dismantle the original safety guard and diamond cutting wheel from the high-speed angle grinder.
- 2. Loosen the connector setting screws in the Dust Collection Cover and leave loose.
- Attach the connector to the wheel guard mount of the high-speed angle grinder. Adjust the angle of the Dust Collection Cover when attaching. (Fig. 1)
- 4. Using a Phillips screwdriver, tighten the two setting screws securely. (Fig. 2)






## ▲ CAUTION!

This Dust Collection Cover is solely designed for application with diamond wheel. Do not use with any other type of tool such as a conventional abrasive cut-off wheel or carbide tip saw blade.


#### ► INSTALLING TO OTHER HIGH-SPEED ANGLE GRINDERS WITH INCLUDED OTHER CONNECTORS

If you install the Dust Collection Cover to a high-speed angle grinder but the connector is loose and cannot be securely attached, it may be necessary to change the connector designed for other makes.


- 1. Using the hexagon Wrench, remove the three bolts in the connector attached to the Dust Collection Cover. (Fig. 3)
- 2. Attach the supplied connector by following the instruction in (1) above in reverse. (For Hitachi Grinder use Part No: 500003/ for Metabo / Bosch use Part No: 500004)
- 3. Subsequent procedures are the same as for attaching the adapter to a high-speed angle grinder in case changing the connector is not needed.




► MOUNTING THE DIAMOND WHEEL




1. Loosen the Dust Collection Cover Knob (A). (Fig. 4)




2. Slide the Dust Collection Cover open. (Fig.5)




- 3. Mount the supplied spacer with the power tool or dedicated flange lock nut set on the spindle and then mount the diamond wheel. (Fig. 6)
- 4. Mount the inner flange on the spindle on top of the diamond wheel with the convex side of the inner flange on the diamond wheel side.
- 5. Press the lock pin to fix the spindle and securely tighten the lock nut with a pin wrench.
- 6. Replace the Dust Collection Cover (Fig. 4) and tighten the knob (A).



 Use D115 scale for 4.5" (115mm) diameter blade and D125 scale for 5" (125mm) diameter blade. Cutting depth is indicated by millimeter.



► ATTACHING THE DUST COLLECTOR




Attach the Dust Collection Cover to the hose. (Fig. 10)

\*The hose opening of the Dust Collection Cover has an outside diameter of 34mm.

If necessary, use the Rubber Hose Adapter and Stainless Hose Band supplied with the Dust Collection Cover.

### ► ALPHA<sup>®</sup> ECOGUARD TYPE W SCHEMATIC



#### ► ALPHA® ECOGUARD TYPE W PARTS LIST

DRAWING NO.	PART NO.	DESCRIPTION	QUANTITY
1	500027	Cover Assembly	1
2	500009	Base	1
3	500010	Base Plate	1
4a	500002	Connector Assembly (Alpha®/Makita®/ Milwaukee)	1
4b	500003	Connector Assembly (Hitachi)	1
4c	500004	Connector Assembly (Metabo®)	1
4d	500027	Connector Assembly (Bosch®/Dewalt)	1
5	500005	Rubber Hose Adapter	1
6	500006	Stainless Steel Hose Band	1
7	500007	Inner Flange	1
8	500008	Lock Nut	1
9e	500011	Spacer (Hitachi/T2.5)	1
9f	500012	Spacer (Metabo <sup>®</sup> /T5.0)	1
10	500015	Knob Bolt	2
11	500016	Shaft	1
12	500017	Screw	2
13	500018	Spring Washer	4
14	500019	Washer	3
15	500020	Flat Head Screw	3
16	500021	Taper Washer	3
17	500025	Brand Label	1
18	500022	Collar - M	1
19	500024	Hex. Wrench	1
20	210105	Pin Wrench	1
21	500035	Collar D	1
Optional Accessory:			
Shown on pg 4	500026	Flexible Connector Hose 18"	1



103 Bauer Drive, Oakland, NJ 07436 • 800-648-7229 • Fax: 800-286-0114 www.alpha-tools.com

Copyright © 20102Alpha Professional Tools. All rights reserved.