# HIGH-PERFORMANCE PNEUMATIC POLISHER



## The Best even got Better with...

#### • OIL PORT

NEW

Easy access to execute daily maintenance

#### ENHANCED SPINDLE

Taller wrench slot for easy tool removal with standard spanner (included)

### 15' FLEXZILLA® AIR AND WATER HOSES

Extreme all weather flexibility (-40° to +140° F)

Specifications:	Equipment Included:
Air Pressure         85 PSI Air           Consumption         15CFM           Speed (no load)         4,000 RPM           Weight         2.64lbs/1.2kg           Air Inlet         1/4" BSPP           Water Inlet         1/8" BSPP           Spindle         5/8"-11	<ul> <li>Air Lead Hose - (15ft. / 4.5m)</li> <li>Water Hose - (15ft. / 4.5m)</li> <li>Side Handle (reversible)</li> <li>Double End Wrench (19mm / 22mm)</li> <li>Rust Inhibitor Oil (8oz / 237ml) (AIR-008)</li> <li>Screw (w/ O- Ring Seal for Oil Port)</li> <li>Exhaust Hose with Clamp</li> </ul>

PART NO.	DESCRIPTION
AIR-680	Air Polisher
AIR-008	Rust Inhibitor Oil for Pneumatic Tools (8oz / 237ml)

## 🤣 Alpha Professional Tools®

103 Bauer Drive, Oakland, NJ 07436 • 800-648-7229 • Fax: 800-286-0114 www.alpha-tools.com

Copyright © 2015 Alpha Professional Tools. All rights reserved.