# Safety DATA SHEET DOCUMENT NO.: 517 | DATE PUBLISHED: 05/31/15

# Alpha Professional Tools®

For chemical emergency spill, leak, fire, exposure or accident call (CHEMTREC) 800-424-9300. This SDS complies with 29 CFR 1919.1200 (The OSHA Hazard Communication Standard).

**Section 1: Identification** Product / Chemical Name: **Lubricating Grease Distributor Name:** Product Identification No: GLA, NLGI #0 GLB, NLGI #1 GLC, NLGI #2 Alpha Professional Tools® Chemical Family: N/A Address: **Trade Name and Synonyms:** 103 Bauer Drive, Oakland, NJ 07436 High Temperature MP Synthetic Lithium Complex Grease **Emergency Tel. No.:** Molecualar Weight: N/A 800-648-7229 Chemical Name: N/A Chemical Formula: N/A Material Use: N/A Section 2: Hazard(s) Identification POTENTIAL HEALTH EFFECTS: Minor eye, inhalation and skin irritant.

\*See Section 11 for toxicological information.

Section 3: Composition/Information on Ingredients

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200) This product is not formulated to contain ingredients that have exposure limits exceeding those established by US agencies.

#### **NFPA & HMIS Rating**

Red Flammability: 1Yellow Reactivity: 0Blue Health: 2White Special: N/A

\*See Section 8 for exposure limits.

Section 4: First-Aid Measures		
tention if irritation develops.broap <b>SKIN:</b> Wash immediately with soap and water. Remove contaminated clothing and launder before reuse. Discard shoes and leather articles saturated with the product. Ob- tain medical advice if irritation occurs.IN 2 or high	NHALATION: Remove exposed person to fresh air. If preathing is labored give oxygen. If breathing has stopped pply artificial respiration. Get immediate medical atten- ion. NGESTION: DO NOT INDUCE VOMITING. If conscious, give glasses of water. If vomiting does occur, keep head below ips to reduce risk of aspiration. Get immediate medical ttention.	

⊃opyright © 2015 Alpha Professional Tools. All rights reservec

Page 1 of 4

### **Section 5: Fire-Fighting Measures**

Flash Point: 450F(232C) Method: COC ASTM D-92 LFL/UFL: Not Determined Auto-ignition Temperature: Not Determined **EXTINGUISHING MEDIA:** Carbon dioxide, dry chemical, and alcohol foam.

**FIREFIGHTING EQUIPMENT:** Full bunker gear recommended including a positive pressure self-contained breathing apparatus.

## Section 6: Accidental Release Measures

Isolate spill area. Provide adequate ventilation. Wear appropriate personal protection. Recover free product for recycle and/ or disposal. Add sand, earth or other suitable absorbent to spill area. Prevent entry into sewers and waterways. Check under Transportation and Labeling (DOT/CERCLA) and Other Regulator Information Section (SARA) for hazardous substances to determine regulatory reporting requirements for spill.

Section 7: Handling and Storage		
<b>HANDLING:</b> Keep containers closed. Avoid contact with eyes, skin or clothing. Wash hands after handling. Empty container may retain product residue which may exhibit hazards of product.	<b>STORAGE:</b> Keep away from heat or flame.	
Section 8: Exposure Controls/Personal Protection		
<b>VENTILATION:</b> Use adequate general or local exhaust ven- tilation to keep airborne concentrations below exposure limits. <b>RESPIRATORY:</b> Use a NIOSH approved respirator when necessary.	<ul> <li>SKIN: Use Viton or Nitrile gloves to avoid prolonged or repeated skin contact.</li> <li>EYE: Use splash goggles or face shield where splashing is expected or can occur.</li> <li>EXPOSURE LIMITS: The Threshold Limit Value (TLV) of 5 mg/m3 is suggested for oil mist.</li> </ul>	

# **Section 9: Physical and Chemical Properties**

Physical State: Semi-Solid Boiling Point: 600F(316C) Melting Point: 500F(260C) Vapor Pressure: Not Determined Vapor Density (Air=1): Negligible Evaporation Rate: Not Determined Solubility in Water: Negligible Specific Gravity (Water=1): 0.8900 Volatility (Volume): Negligible VOC: Unknown pH: Essentially Neutral Odor: Mild, Bland Odor Odor Threshold: Not Determined Appearance: Red Semi-Solid

#### Viscosity, cSt @ 100C: GLA, NLGI #0: 13 GLB, NLGI #1: 14 GLC, NLGI #2: 18

#### Viscosity, cSt @ 40C:

GLA, NLGI #0: 110 GLB, NLGI #1: 110 GLC, NLGI #2: 155

## Section 10: Stability and Reactivity

**STABILITY:** Stable under moderately elevated temperatures and pressures.

**INCOMPATIBILITY:** Avoid contact with strong oxidants.

HAZARDOUS POLYMERIZATION: Will not occur. HAZARDOUS DECOMPOSITION OF PRODUCT: Toxic oxides of carbon, aldehydes

Section 11: Toxicological Information		
<b>ACUTE EXPOSURE</b> <b>Eye Irritation:</b> Moderate to strong eye irritation. Based on data from components or similar material.	<b>CHRONIC EXPOSURE</b> <b>Chronic Toxicity:</b> No data available to indicate product present at greater than 1.0% are chronic health hazards.	
<b>Skin Irritation:</b> Not expected to be a primary skin irritant. Based on data from components or similar material. Pro- longed or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include red-	<b>Carcinogenicity:</b> No data available to indicate product present at greater than 0.1% are a carcinogenic hazard. <b>Mutagenicity:</b> No data available to indicate product present at greater than 1.0% present a mutagenic or genotoxic hazard.	
ness, edema, drying, defatting, and cracking of the skin. <b>Respiratory Irritation:</b> If material is misted or if vapors are	<b>Reproductive Toxicity:</b> No data available to indicate product present at greater than 1.0% present a reproductive hazard.	
generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract similar to that observed with mineral oil. Based on data from	<b>Teratogenicity:</b> No data available to indicate product present at greater than 1.0% present a teratogenic hazards.	
components or similar materials. Under good industrial hygiene practices where all exposure limits are observed, respiratory irritation should not be a problem.	ADDITIONAL INFORMATION Exposure Limits: Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter.	

Section 12: Ecological Information (non-mandatory)

No data available on the adverse effects of this product on the environment.

Section 13: Disposal Considerations (non-mandatory)

If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

# 103 Bauer Drive, Oakland, NJ 07436 • 800-648-7229 • Fax: 800-286-0114 www.alpha-tools.com

#### Section 14: Transport Information (non-mandatory)

This product is not classified as hazardous material for DOT shipping. For further information relative to spills resulting from transportation incidents, refer to the latest DOT Emergency Response Guidebook for Hazardous Materials.

### Section 15: Regulatory Information (non-mandatory)

U.S. Federal Regulations OSHA Table Z: Synthetic Base Stock (mist) **TSCA:** All components of this material are listed on the U.S. TSCA Inventory. CERCLA 40 CFR 302.4: Zinc and Compounds@ 0-2%, Statutory RQ 1 lb

SARA Title III Section 302 Extremely Hazardous : Not Applicable Section 311/312 Fire Hazard: Yes Reactive Hazard: No Release of Pressure: No Acute Health Hazard: Yes Chronic Health Hazard: No Section 313 Toxic Chemical: Not Applicable

U.S. State Regulations California (Prop 65) Does not contain chemicals known to the state of California to cause cancer.

International Regulations WHMIS: All components listed

**Section 16: Other Information** 

SDS Date of issue: 17th October, 2005 SDS Date Revised: 9th February, 2012

Prepared By: Manufacturer's Technical Services Department

#### Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

# 🕗 Alpha Professional Tools°

103 Bauer Drive, Oakland, NJ 07436 • 800-648-7229 • Fax: 800-286-0114 www.alpha-tools.com